

FEATURES AND PERFORMANCE

Angular outreach of telescopic arm	From 0° to +75°
Arm articulations	2 + telescopic
Max. drive-motion speed	1.5 km/h
Rubber tracks	180x34x72
Traction	Hydraulic
Max. incline	28%
Length	4000 mm
Width (without platform)	780 mm
Height	1,960 mm
Max. operating height	14.00 m/1 operator - 12.30 m/2 operators
Max. operating outreach	6.40 m/1 operator - 5.70 m/2 operators
Maximum capacity	120-200 kg/1-2 operators
Maximum number of operators	2
Dimensions of aluminium removable operator platform	1400 x 700 x h1100 mm
Controls	Hydraulic
Turret rotation	300°
Engine	One-cylinder Honda
Running weight	1850 kg 1630

OPTIONALS AVAILABLE ON REQUEST

- Pair of white trace tapes for internal use
- 60W illuminating lamp on operator platform supplied by vehicle's batteries (available only with optional power socket), including 12V power socket
- Inclinator with acoustic alarm that is set off when permitted incline is exceeded
- Multiuse power line to platform
- Engine: Lombardini, diesel
- Enlarged plates in nylatron, d. 300
- Adhesive messages on arm
- Paint other than standard (white RAL 9016)
- Platform waxing for sea transport
- 2 safety belts



OPERATING AREA AND GEOMETRICAL FIGURES

